

SHORE MATE®

FIRST BY DESIGN

BOAT LIFTS & DOCKS

Specification Sheet

Lift Model: L4500H

Weight Capacity:	4500#	Type of Lift:	Cantilever/ HYD.
Maximum Beam:	120"	Application:	Sport / Cruise
Weight	425#	Lift Dimensions:	150" L x 126" W
Lifting Height:	48"	Foot Pad Dim:	16" L x 8" W
Min. Water Depth:		Leg Length:	36"
Power Source:	12V DC	Bunk Length:	12'

Standard Equipment:

12' Pivoting Vinyl Bunks
Battery Connector Cables (Battery Not Included)
Beam 120"
Hydraulic Pump w/ Quick Connect Hoses, Pre-Charged Lines and Fluid
Stainless Steel Fasteners
(2) 2.5" Stainless Steel Cylinders w/ Brass Rod Scrapers
36" Lift Legs (Set of 4)
All Aluminum Frame
Hand Control Unit w/ Extended Cord
Lockable and Durable "Poly Hopper" for Pump and Battery Storage

Accessories:

Lift Legs: Longer Per Foot
Lift Transport Kit
Vertical Load Guides
12' Side Step Guides
Radio Remote Control w/ 2 Key Fobs
Solar Panel: 10 Watt
Solar Panel Holder (Mounts to Upright)
AC Charge Pack (In Place of Solar Panel)

Part #

LSA0251
LSA0020
LSA1121V
LSA1120
LSAH020
LSAH014
LSAH017
LSAH100

**Pontoon Conversion Kit: Center or Bunk
Tri-Toon Lift Kit
Underwater Light Kit: New Lifts Only
Canopy**

**LSA0122
LSA0130
LSAH016**