SHORE-MATE®
FIRST BY DESIGN

BOAT LIFTS & DOCKS

SPECIFICATION SHEET

Lift Model: L1200HD

Weight Capacity:	1200#	**Type of Lift:**	Cantilever/ HYD
Maximum Beam:	114” / 120”	**Application:**	PWC
Weight:	350#	**Lift Dimensions:**	132” L x 120” W
Lifting Height:	32”	**Foot Pad Dim:**	16” L x 9” W
Min. Water Depth:	16” Plus Draft	**Leg Length:**	36”
Power Source:	12V DC	**Bunk Length:**	8’

Standard Equipment

- 8’ Pivoting Vinyl Bunks
- Battery Connector Cables (Battery Not Included)
- Beam 60” / 80”
- Hydraulic Pump w/ Quick Connect Hoses, Pre-Charged Lines and Fluid
- Stainless Steel Fasteners
- (2) Stainless Steel Rod High Performance Cylinder
- 36” Lift Legs (Set of 4)
- All Aluminum Frame
- Hand Control Unit w/ Extended Cord
- Lockable and Durable “Poly Hopper” for Pump and Battery Storage

Accessories	Part #
Lift Legs: Longer Per Foot	LSA0x53
Lift Transport Kit	LSA0020-H
Radio Remote Control w/ 2 Key Fobs	LSAH020
Solar Panel: 10 Watt	LSAH014
Solar Panel Holder (Mounts to Upright)	LSAH017
AC Charge Pack (In Place of Solar Panel)	LSAH100