SHORE-MATE®
FIRST BY DESIGN

BOAT LIFTS & DOCKS

SPECIFICATION SHEET

Lift Model: L30000H

Weight Capacity:	30000#	**Type of Lift:**	Cantilever/ HYD
Maximum Beam:	168"	**Application:**	Sport / Cruise
Weight:	2750#	**Lift Dimensions:**	TBD
Lifting Height:	63”	**Foot Pad Dim:**	18” L x 15” W
Min. Water Depth:	26” Plus Draft	**Leg Length:**	48”
Power Source:	12V DC	**Bunk Length:**	(6) 8'

Standard Equipment

- (6) 8' Pivoting Vinyl Bunks
- Battery Connector Cables (Battery Not Included)
- Beam 168"
- Hydraulic Pump w/ Quick Connect Hoses, Pre-Charged Lines and Fluid
- Stainless Steel Fasteners
- (4) 4” Stainless Steel Cylinders w/ Brass Rod Scrapers
- 48” Lift Legs (Set of 4)
- All Aluminum Frame
- Hand Control Unit w/ Extended Cord
- Lockable and Durable Fiberglass Box for Pump and Battery Storage

Accessories	Part #
Lift Legs: Longer Per Foot	LSA0x53
Radio Remote Control W/ 2 Key Fobs	LSAH020
Solar Panel: 20 Watt	LSAH0120
AC Charge Pack (In Place of Solar Panel)	LSAH100