SHORE-MATE®
FIRST BY DESIGN

BOAT LIFTS & DOCKS

SPECIFICATION SHEET

Lift Model: L4500H

Weight Capacity:	4500#	**Type of Lift:**	Cantilever/ HYD
Maximum Beam:	130"	**Application:**	Sport / Cruise
Weight:	425#	**Lift Dimensions:**	150” L x 136” W
Lifting Height:	48”	**Foot Pad Dim:**	16” L x 9” W
Min. Water Depth:	” Plus Draft	**Leg Length:**	36”
Power Source:	12V DC	**Bunk Length:**	12'

Standard Equipment

- 12' Pivoting Vinyl Bunks
- Battery Connector Cables (Battery Not Included)
- Beam 130”
- Hydraulic Pump w/ Quick Connect Hoses, Pre-Charged Lines and Fluid
- Stainless Steel Fasteners
- (2) 2.5” Stainless Steel Cylinders w/ Brass Rod Scrapers
- 36” Lift Legs (Set of 4)
- All Aluminum Frame
- Hand Control Unit w/ Extended Cord
- Lockable and Durable Fiberglass Box for Pump and Battery Storage

Accessories	Part #
Lift Legs: Longer Per Foot	LSA0x53
Lift Transport Kit	LSA0020
Vertical Load Guides	LSA1121H
Adjustable In-between Upright Step	LSA1122H
Radio Remote Control W/ 2 Key Fobs	LSAH020
Solar Panel: 20 Watt	LSAH0120
Solar Panel Holder (Mounts to Upright)	LSAH017
AC Charge Pack (In Place of Solar Panel)	LSAH100
Pontoon Conversion Kit: Center Lift or Bunk	LSA0122
Tri-Toon Kit	LSA0132